## पेटेंट कार्यालय शासकीय जर्नल

## OFFICIAL JOURNAL OF THE PATENT OFFICE

निर्गमन सं. 16/2024 ISSUE NO. 16/2024

शुक्रवार FRIDAY दिनांकः 19/04/2024 DATE: 19/04/2024

पेटेंट कार्यालय का एक प्रकाशन PUBLICATION OF THE PATENT OFFICE (19) INDIA

(22) Date of filing of Application :27/02/2024 (43) Publication Date: 19/04/2024

(54) Title of the invention: A UNIVERSAL CHAIR-SIDE ORTHODONTIC HANDY SPOT WELD-ER WITH A SPRING-LOADED HANDLE

:H02M0003335000, B23K0011110000, (51) International F02P0015100000, B23K0009100000, classification

A61B0017120000

(86) International :NA Application No :NA Filing Date (87) International

: NA Publication No

(61) Patent of Addition:NA to Application Number :NA Filing Date

(62) Divisional to :NA **Application Number** :NA Filing Date

(71)Name of Applicant:

1)JSS Dental College and hospital, JSS Academy of Higher **Education & Research** 

Address of Applicant :Sri Shivarathreeshwara Nagara, Mysuru, Karnataka, India 570015 Mysore -----

Name of Applicant: NA Address of Applicant: NA (72) Name of Inventor: 1)Dr. I Girish Kumar

Address of Applicant: Department of Orthodontics & Dentofacial Orthopedics, JSS Academy of Higher Education & Research,

Mysore Mysore -----

2)Dr. Raghunath N

Address of Applicant: Department of Orthodontics & Dentofacial Orthopedics, JSS Academy of Higher Education & Research, Mysore Mysore -----

3) Javachandran PP.

Address of Applicant: Department of Dental Mechatronics, JSS Academy of Higher Education & Research, Mysore, Mysore -----

## (57) Abstract:

A UNIVERSAL CHAIR-SIDE ORTHODONTIC HANDY SPOT WELDER WITH A SPRING-LOADED HANDLE ABSTRACT 5 A universal orthodontic handy spot welder (200) is provided. The welder in cludes a spring-loaded handle (100) for welding in an orthodontic procedure. The welder further includes a transformer (212) including a primary coil (218) and a secondary coil (220) for controlling a voltage supplied to the spring 10 loaded handle (100). The welder further includes a main switch (206) for con trolling the circuit of the primary coil (218). The welder further includes a fuse (204) connected between the main switch (206) and a power supply (202). The welder further includes a foot control (208) connected between the main switch (206) and the primary coil (218) for controlling the intensity of welding per 15 formed using the spring-loaded handle (100), by a user. The welder further in cludes a weld intensitometer (210) configured for controlling an intensity of welding and connected between the primary coil (218) and the main switch (206). 20 Figures 2 and 5

No. of Pages: 21 No. of Claims: 4